

RUBIG
DRIVING SUCCESS

Top of Nitriding and Coating

Nitriding and Coating Furnaces





Plasma Nitriding Systems & Plasma Coating System

Innovative heat treatment solutions in plasma nitriding and plasma coating

MICROPULS® Technology from RUBIG Industrial Furnaces is the premium plasma technology in the heat treatment sector. RUBIG partners from across the globe have confidence in this plasma nitriding technology. The customers benefit from over 25 years of development experience in the field of customized thermal treatment systems for a variety of sectors, from job-shop heat treatment operations to fully automated industrial companies.

Benefits of the RUBIG MICROPULS® Systems:



Modularity

Flexible systems, perfect for in-house sourcing and future upgrades



Industry 4.0

Simple data exchange with supervising control and ERP systems



Capacities

Increased degree of filling for cost-effective plasma nitriding



Temperature control

Independently controlled heating and cooling zones and temperatures are measured directly at the component



Efficient operation

Remote maintenance and online diagnostics for increased efficiency



MICROPULS® Technology

Perfect process control using powerful plasma generators



SiR concept


Improved surfaces plus cost savings of up to 20 %



Environmental compatibility

Optimum energy efficiency and lowest emissions

All systems are AMS and CQI9 suitable.



MICROPULS® EVEREST



The Plasma Nitriding System

MICROPULS® EVEREST allows RUBIG customers to benefit from PLASNIT®, PLASNIT®C and PLASOX® processes.

Longer service life

Lower distortion levels and increased strength

Short process chain

Minimizes hard fine machining and mechanical masking

Stability

Reproducible processes for increased reliability

Flexibility

Variable layer structure, also for complex geometries

Diversity

PLASNIT®C and PLASOX® processes allow for additional tribology and corrosion critical applications

Environmental friendliness

No use of toxic gases

Classic applications

- Shafts (crankshafts, camshafts, geared shafts, ...)
- Gears (hollow gears, pinions, ...)
- Valves
- Bearing parts (bearing rings, bearing ball, ...)
- Tool shapes
- Machine components

- Dies
- Spindles and screws
- Screw fittings from high chromium steels

STANDARD SYSTEMS & THEIR SIZES

useful diameter x useful height in mm

400 x 600	1.500 x 2.100
700 x 1.200	1.500 x 2.400
1.000 x 1.800	1.500 x 2.700

All the systems are available in SINGLE, DUO or TANDEM design. Special sizes on request.



MICROPULS® PROCOAT

The Coating System

MICROPULS® PROCOAT is the optimum system solution in the field of hard coatings. From mold making and job-shop coating to component coating.

Wide choice of processes

RUBIG offers a great variety in PLASTIT® processes to meet customers requirements

Diversity

Wide application range for multilayer, gradient or nanocomposite coatings

Reduced temperatures

Lower distortion levels at lower treatment temperatures

Industry solutions

From die-cast aluminum and plastic injection molding to food processing

Wide range of applications

Large and complex parts are coated evenly

Flexibility

Variable layer structure, also for complex parts

DUPLEX processes

Our all-in-one solution ensures lower unit costs



Classic applications

- Plastic injection moulds
- Molds for aluminum
- Deep drawing mandrels

STANDARD SYSTEMS & THEIR SIZES

useful diameter x useful height in mm

400 x 600	1.500 x 1.800
700 x 900	1.500 x 2.100
1.000 x 1.500	

All the systems are available in SINGLE, DUO or TANDEM design. Special sizes on request.



MICROPULS® DIAMOND Xtended

The DLC Coating System

With the MICROPULS® DIAMOND Xtended system RUBIG offers one of the most innovative system solutions in the field of DLC coating technology. The system helps RUBIG customers realize the DLC Xtended® process.

Internal coating

For complex geometries and increased wear protection

Thick layers

For a longer service life and improved corrosion protection

Improved characteristics

Low temperatures reduce distortion levels

Cost savings

Less post processing and mechanical masking save time and costs

Homogeneity

Three-dimensional coating without part rotation

Wide range of applications

Large and complex parts are coated evenly

Flexibility

Variable layer structure, also for complex parts

Classic applications

- Pipes
- Ball studs
- Pistons

STANDARD SYSTEMS & THEIR SIZES

useful diameter x useful height in mm

700 x 1.130
850 / 1.000 x 1.650
1.300 / 1.500 x 2.330

All the systems are available in SINGLE, DUO or TANDEM design. Special sizes on request.





Gas Nitriding Systems

The GASCON technology stands for highly efficient and advanced gas nitriding

RUBIG Industrial Furnaces GASCON technology stands for highly efficient and advanced gas nitriding. Constructed in a modular way and adapted according to customer needs, these systems prove themselves through their excellent durability and the possibility to control processes by means of nitriding potential.

Benefits of the RUBIG Systems:



Modularity

Flexible plant systems, perfect for in-house sourcing and upgrades in the future



Industry 4.0

Simple data exchange with supervising control and ERP systems



Efficient operation

Remote maintenance and online diagnostics increase your efficiency



Individuality

From standard systems to customer-specific systems and special system solutions



Longevity

Usage of Inconel prolongs lifetime of retort



Controllability

Atmosphere control (K_N , K_C , K_O or dissociation) possible

All systems are AMS und CQI9 suitable.

GASCON K2

The Gas Nitriding System

GASCON K2 helps RUBIG customers realize R.NIT+® and GASOX® processes.

Short process chain

Minimisation of hard finishing through minimal distortion

Stability

Reliability due to reproducible results

Diversity

Other tribology and corrosion critical applications are possible using the GASOX® process

Controllability

Optional K_N control allows optimal reproducibility

Classic applications

- Shafts (crankshafts, camshafts, geared shafts, ...)
- Gears (hollow gears, pinions, ...)
- Valves
- Bearing parts (bearing rings, bearing balls, ...)
- Machine tool parts
- Spindles and screws

Standard systems & their sizes

Special sizes on request

BELL TYPE SIZES

useful diameter x useful height in mm

650 x 1.200	1.500 x 2.100
1.100 x 1.800	1.500 x 2.400

All bell type systems can be provided as a DUO-system.

PIT TYPE SIZES

useful diameter x useful depth in mm

800 x 1.500	1.200 x 3.000
1.000 x 2.000	1.500 x 3.000
1.200 x 2.500	

HORIZONTAL TYPE SIZES

useful width x useful height x useful depth in mm

500 x 500 x 600	900 x 900 x 1.200
600 x 600 x 900	900 x 900 x 1.800



RUBIG

DRIVING SUCCESS

Technical details are subject to change. ©RUBIG 2021

Surface Improvement by RUBIG

The RUBIG SIR program represents the development of equipment and processes to ensure optimal and improved performance for the surface of tools and components made of steel, while protecting the environment! SIR allows a reduction in fine machining, offers production integration, partial

nitriding and process combinations, and ensures a prolonged service life. SIR ensures the lowest emissions, minimal gas consumption and extended product lifetimes. Cost savings of around 20 % are realized by eliminating the need for fine machining.

SIR
Surface Improvement by RUBIG
SAVES MONEY
PROTECTS THE ENVIRONMENT

RUBIG Group

Durisolstr. 12
4600 Wels
AUSTRIA

t +43 (0) 7242 / 293 83
at.office@rubig.com